

MODEL MSB Specifications

Type	MSB7-50	MSB7-60	MSB7-60L
Pitch	7mm	7mm	7mm
Number of shuttles	512	612	612
Diameter of bobbin	185mm(ID110)	185mm(ID110)	200mm(ID90)
Applicable twine range			
Nylon Mono	0.14-0.28(55g)	0.14-0.28(55g)	0.18-0.28
Nylon Multi	110/2~210/9(38g)	110/2~210/9(38g)	210/3~210/9
PE twine	250/2~380/4(33g)	250/2~380/4(33g)	250/2~380/4
PE Braided	-	-	-
Mesh range (knot to knot)	5.5mm~150mm	5.5mm~150mm	5.5mm~150mm
U/K		-	-
Looming speed(R.P.M.)			
S/K D/K	Up to 28RPM	Up to 26RPM	Up to 25RPM
U/K		-	-
Knot configuration	SINGLE/DOUBLE	SINGLE/DOUBLE	SINGLE/DOUBLE
Type of upper hook			
Main motor	3.7kw * 1	3.7kw * 1	3.7kw * 1
Mesh forwarding motor			
Dimensions	5,950*2,280*1,740	6,680*2,280*1,740	6,680*2,280*1,740
Weight	Net : 7,500kg Gross : 8,800kg	Net : 10,000kg Gross : 11,800kg	Net : 10,000kg Gross : 11,800kg
Packing Size	20.0M3	31M3	31M3

Type	MSB9-40	MSB9-40U	MSB9-50
Pitch	9mm	9mm	9mm
Number of shuttles	412	412	512
Diameter of bobbin	200mm	200mm	200mm
Applicable twine range			
Nylon Mono	0.20~0.40(100g)	0.20~0.40(100g)	0.20~0.40(100g)
Nylon Multi	210/3~210/18(60g)	210/3~210/18(60g)	210/3~210/18(60g)
PE twine	250/3~380/9(50g)	250/3~380/9(50g)	250/3~380/9(50g)
PE Braided	-	-	-
Mesh range (knot to knot)	7.5mm~150mm	7.5mm~150mm	7.5mm~150mm
U/K		27mm~150mm	-
Looming speed(R.P.M.)			
S/K D/K	Up to 28RPM	Up to 28RPM	Up to 25RPM
U/K		Up to 20RPM	-
Knot configuration	SINGLE/DOUBLE	S/K D/K U/K	SINGLE/DOUBLE
Type of upper hook			
Main motor	3.7kw * 1	3.7kw * 1	3.7kw * 1
Mesh forwarding motor			
Dimensions	5,950*2,280*1,740	5,950*2,280*1,740	6,680*2,280*1,740
Weight	Net : 7,500kg Gross : 8,800kg	Net : 7,500kg Gross : 8,800kg	Net : 10,000kg Gross : 11,800kg
Packing Size	20.0M3	20.0M3	31M3

H29.3.24

Note: 1) Looming speed varies in relation to mesh size and twine diameter.
2) Minimum size carries in relation to the operating speed and twine diameter.
3) All specifications are subject to change without notice.