

MODEL MSW Specifications

Type	MSW9-60	MSW11-50	MSW14-40
Pitch	9mm	11mm	14mm
Number of shuttles	612	512	412
Diameter of bobbin	230mm	250mm	250mm
Applicable twine range			
Nylon Mono	0.28-0.40	0.28 - 0.50	0.37 - 0.70
Nylon Multi (S/K)	210d/4-18	210d/6 - 27	210d/9 - 60
Nylon Multi (D/K)	210d/4-15	210d/6 - 21	210d/9 - 45
PE Twine	250d/3 - 380d/9	380d/3 - 380d/15	380d/6 - 380d/30
Mesh range (knot to knot)	7.5mm~150mm	8.5mm~200mm	11mm~200mm
Looming speed(R.P.M)	Up to 20RPM	Up to 18RPM	Up to 18RPM
Knot configuration	SINGLE/DOUBLE	SINGLE/DOUBLE	SINGLE/DOUBLE
Type of upper hook			
Main motor	5.5 kw * 1	5.5 kw * 1	5.5 kw * 1
Mesh forwarding motor			
Dimensions	7,986*4,200*1,600	7,986*4,200*1,600	7,986*4,200*1,600
Weight	Net : 13,500kg Gross : 15,000kg	Net : 13,500kg Gross : 15,000kg	Net : 13,500kg Gross : 15,000kg
Packing Size	38.0M3	38.0M3	38.0M3
Type	MSW18-30	MSW22-20	MSW22-25
Pitch	18mm	22mm	22mm
Number of shuttles	312	212	252
Diameter of bobbin	300mm	300mm	300mm
Applicable twine range			
Nylon Mono	0.40 - 0.90	0.50 - 1.20	0.50 - 1.20
Nylon Multi (S/K)	210d/18-75	210d/24 - 150	210d/24 - 150
Nylon Multi (D/K)		210d/24 - 90	210d/24 - 90
PE Twine	380d/9 - 380d/36	380d/15 - 380d/60	380d/15 - 380d/60
Mesh range (knot to knot)	14mm~200mm	18mm~200mm	18mm~200mm
Looming speed(R.P.M)	Up to 18RPM	Up to 18RPM	Up to 18RPM
Knot configuration	SINGLE/DOUBLE	SINGLE/DOUBLE	SINGLE/DOUBLE
Type of upper hook			
Main motor	5.5 kw * 1	5.5 kw * 1	5.5 kw * 1
Mesh forwarding motor			
Dimensions	7,986*4,200*1,600	7,986*4,200*1,600	7,986*4,200*1,600
Weight	Net : 13,500kg Gross : 15,000kg	Net : 13,500kg Gross : 15,000kg	Net : 13,500kg Gross : 15,000kg
Packing Size	38.0M3	38.0M3	38.0M3

H.29.7

- Note: 1) Looming speed varies in relation to mesh size and twine diameter.
2) Minimum size carries in relation to the operating speed and twine diameter.
3) All specifications are subject to change without notice.